

CHINA

CE,ISO, SGS

Low-E glass

USD1-99/

7 days

D/A

wooden case

20000 Square Meter/Day

Rise

Factory Price Laminated Low-E Glass Insulated for Window / Building

T/T, L/C, D/P, Western Union, MoneyGram,

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: 1 container
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:



青島讓致設護科技有限公司

Product Specification

 Application: 	Windows/Doors/Walls			
 Keywords: 	Laminated Glass, Tempered Glass, Low-E Glass, Fire Resitance Tempered Laminated Glass, Safety GLASS			
 Glass Application: 	Building, Furniture, Automotive, Etc.			
• Film:	Customized			
 Glass Shape: 	Flat, Curved, Etc.			
 Sound Insulation: 	Good			
 Specification: 	Cutomsized			
• Shape:	Flat			
 Low E Coating: 	Yes			
 Energy Saving: 	Yes			
• Usage:	Door, Building, Window			
Highlight:	Window Low-E Glass Insulated, Factory Price Low-E Glass Insulated,			

Building Low-E Glass Insulated



More Images



Product Description

Layer Type	Low-E Laminated Glass			
Function	Decorative			
Intermediate Film	PVB			
Melting Point	High Temperature			
Production	Dry Laminated Glass			
Color	Clear			
Usage	Furniture, Building, Window			
Delivery Time	15-20 Days			
HS	7005100000			
PVB Color	Blue, Green, Gray, Bronze and Milk White,			
PVB Thickness	0.38mm, 0.76mm, 1.14mm, 1.52mm etc			
Edge Work	Flat Polished			
Quality Standard	GB 15763.3-2009			
Layers	Multi Layers Upon Your Request			
PVB Brand	Decent, Saflex, Sentryglas			
Application	Architecture, Furniture			
Interlayers	PVB/EVA/Sgp/PU/Sgx/Xir			
Thickness	5.38mm6.38mm/6.76mm/8.38 mm/8.76mm/10.38mm/10.76m m/			
Size	According to The Client' S Requirement			
Technique	Laminated			
Payment	T/T			
Certificate	CE,ISO, SGS			
Transport Package	Wooden Case			
Specification	1702 mm-2800 mm			
Trademark	Rise			
Origin	China			
HS Code	7007290000			

Low-E Glass: Recognized for its energy-saving properties, this glass product incorporates a microscopically thin coating that reflects heat back into the room. By minimizing heat transfer, it reduces energy consumption for heating and cooling, resulting in lower utility costs. Additionally, it enhances thermal insulation, improves comfort levels, and contributes to environmentally friendly building practices.

Details:

r roddellorr Oapaerty			20	ooo oquai					
	Product performance index								
Piece	thickness	Visible light transmittance	Square re Before steel	After steel	Product application	remarks			
FGA7	4 ~ (79	6.5 <r<8< td=""><td>6<r<8< td=""><td>Electric heating / thermal reflection</td><td></td></r<8<></td></r<8<>	6 <r<8< td=""><td>Electric heating / thermal reflection</td><td></td></r<8<>	Electric heating / thermal reflection				
FGA10	3.2/4/5	82	8 <r<10.3< td=""><td>8<r<10< td=""><td>Electric heating / thermal reflection</td><td>The customer can</td></r<10<></td></r<10.3<>	8 <r<10< td=""><td>Electric heating / thermal reflection</td><td>The customer can</td></r<10<>	Electric heating / thermal reflection	The customer can			
FGA12	3.2/4/5	82.5	12 <r<14< td=""><td>11. 5<r<13. 5<="" td=""><td>Electric heating / thermal reflection</td><td>customize the steel</td></r<13.></td></r<14<>	11. 5 <r<13. 5<="" td=""><td>Electric heating / thermal reflection</td><td>customize the steel</td></r<13.>	Electric heating / thermal reflection	customize the steel			
FGA15	3.2/4/5	83	13 <r<15< td=""><td>12.5<r<15< td=""><td>Electric heating / thermal reflection</td><td>rear resistance</td></r<15<></td></r<15<>	12.5 <r<15< td=""><td>Electric heating / thermal reflection</td><td>rear resistance</td></r<15<>	Electric heating / thermal reflection	rear resistance			
FGA17	3.2/4/5	84	16.5 <r<18.5< td=""><td>16<r<18< td=""><td>Electric heating / thermal reflection</td><td>according to the</td></r<18<></td></r<18.5<>	16 <r<18< td=""><td>Electric heating / thermal reflection</td><td>according to the</td></r<18<>	Electric heating / thermal reflection	according to the			
FGA25	3.2/4/5	83	25 <r<28< td=""><td>23<r<27< td=""><td>Electric heating / thermal reflection</td><td>demand, which is 8-</td></r<27<></td></r<28<>	23 <r<27< td=""><td>Electric heating / thermal reflection</td><td>demand, which is 8-</td></r<27<>	Electric heating / thermal reflection	demand, which is 8-			
FGA29	3.2/4/5	85	30 <r<37< td=""><td>27. 5<r<32. 5<="" td=""><td>Electric heating / thermal reflection</td><td>1100 (0hms / sqm),</td></r<32.></td></r<37<>	27. 5 <r<32. 5<="" td=""><td>Electric heating / thermal reflection</td><td>1100 (0hms / sqm),</td></r<32.>	Electric heating / thermal reflection	1100 (0hms / sqm),			
FGA32	3.2/4/5	85	32 <r<42< td=""><td>30. 5<r<36. 5<="" td=""><td>Electric heating / thermal reflection</td><td>and the square</td></r<36.></td></r<42<>	30. 5 <r<36. 5<="" td=""><td>Electric heating / thermal reflection</td><td>and the square</td></r<36.>	Electric heating / thermal reflection	and the square			
FGA70	3.2/4/5	84. 5	90 <r<100< td=""><td>63<r<69< td=""><td>Electric heating</td><td>resistance</td></r<69<></td></r<100<>	63 <r<69< td=""><td>Electric heating</td><td>resistance</td></r<69<>	Electric heating	resistance			
FGA180	3.2/4/5	83	250 <r<280< td=""><td>170<r<190< td=""><td>Electric heating</td><td>measurement is</td></r<190<></td></r<280<>	170 <r<190< td=""><td>Electric heating</td><td>measurement is</td></r<190<>	Electric heating	measurement is			







Packaging &

Shipping

Laminated Tempered Glass 6.38/10.38/16/12 /13.52 mm Low Iron Polished Edge Tempered Laminated Glass

After Sales

Service

1. Provide you with timely, professional, and efficient services in accordance with standardized service processes; 2. 7 * 24-hour hotline telephone online service;

3. Quality issues that belong to the production process will be unconditionally resolved;

FAQ

Q: What is the MOQ?A: Generally, there is no MOQ for processed glass, but if you want to receive the best price, the bigger quantity, the better price. **Q:** Can I have a small sample to verify the quality?A: Sure, we welcome samples to be tested and checked for quality. **Q:** Can I visit your factory?A: Yes, we welcome all of the customers to visit our factory when you have real requirements, we will take you to each of our production lines, and discuss orders in our office. **Q:** Do you offer a guarantee for the products?A: Yes, generally, we offer 5 years warranty for processing glass based on your normal uses, we advise you use it in the right way can keep your product's service life a long time (more than 5 years). **Q:** How do you control the quality of your products?A: We have standard management in the factory based on the ISO system, and train our staff regularly, our production department will choose high-quality materials for glass strictly, for finished excellent products. And we have QC for each process, once find any problem, we will replace the glass, to make sure every piece of glass go to the customer's warehouse is in good condition.





leon@qdcrglass.com 📀 rise-glass.com

Tianzhi Building, No. 63 Beijing Road, Huangdao District, Qingdao City, Shandong Province