

Doors High Quality Online Low E Glass with Ce ISO Certificate

Basic Information

Place of Origin: CHINABrand Name: Rise

Certification: CE,ISO, SGS
Model Number: Low-E glass
Minimum Order Quantity: 1 container
Price: USD1-99/
Packaging Details: wooden case
Delivery Time: 7 days

Payment Terms: T/T, L/C, D/P, Western Union, MoneyGram,

D/A

Supply Ability: 20000 Square Meter/Day



Product Specification

Application: Windows/Doors/Walls

• Keywords: Laminated Glass, Tempered Glass, Low-E

Glass, Fire Resitance Tempered Laminated

Glass, Safety GLASS

• Glass Application: Building, Furniture, Automotive, Etc.

Film: CustomizedGlass Shape: Flat, Curved, Etc.

Sound Insulation: GoodSpecification: CutomsizedShape: Flat

Shape: FlatLow E Coating: YesEnergy Saving: Yes

• Usage: Door, Building, Window

• Highlight: Online Low-E Glass, Doors Low-E Glass,

High Quality Low-E Glass



More Images





Product Description

Layer Type	Low-E Laminated Glass
Function	Decorative
Intermediate Film	PVB
Melting Point	High Temperature
Production	Dry Laminated Glass
Color	Clear
Usage	Furniture, Building, Window
Delivery Time	15-20 Days
HS	7005100000
PVB Color	Blue, Green, Gray, Bronze and Milk White,
PVB Thickness	0.38mm, 0.76mm, 1.14mm, 1.52mm etc
Edge Work	Flat Polished
Quality Standard	GB 15763.3-2009
Layers	Multi Layers Upon Your Request
PVB Brand	Decent, Saflex, Sentryglas
Application	Architecture, Furniture
Interlayers	PVB/EVA/Sgp/PU/Sgx/Xir
Thickness	5.38mm6.38mm/6.76mm/8.38 mm/8.76mm/10.38mm/10.76m m/
Size	According to The Client' S Requirement
Technique	Laminated
Payment	T/T
Certificate	CE,ISO, SGS
Transport Package	Wooden Case
Specification	1702 mm-2800 mm
Trademark	Rise
Origin	China
HS Code	7007290000
Production Capacity	20000 Square Meter/Day

Low-E Glass: Renowned for its energy-saving performance, this glass innovation incorporates a microscopically thin coating that effectively reflects heat while retaining visible light transmission. By reducing heat transfer, it minimizes the need for heating and cooling, resulting in substantial energy savings and reduced carbon emissions. With enhanced insulation properties, it creates a comfortable and sustainable indoor environment, contributing to green building practices and promoting energy efficiency in architectural design.

Details:

Product performance index							
Piece	thickness	Visible light transmittance	Square re Before steel	sistance After steel	Product application	remarks	
FGA7	4 4	79	6, 5 <r<8< td=""><td>6<r<8< td=""><td>Electric heating / thermal reflection</td><td></td></r<8<></td></r<8<>	6 <r<8< td=""><td>Electric heating / thermal reflection</td><td></td></r<8<>	Electric heating / thermal reflection		
FGA10	3. 2/4/5	82	8 <r<10.3< td=""><td>8<r<10< td=""><td>Electric heating / thermal reflection</td><td>The customer can</td></r<10<></td></r<10.3<>	8 <r<10< td=""><td>Electric heating / thermal reflection</td><td>The customer can</td></r<10<>	Electric heating / thermal reflection	The customer can	
FGA12	3. 2/4/5	82. 5	12 <r<14< td=""><td>11. 5<r<13. 5<="" td=""><td>Electric heating / thermal reflection</td><td>customize the steel</td></r<13.></td></r<14<>	11. 5 <r<13. 5<="" td=""><td>Electric heating / thermal reflection</td><td>customize the steel</td></r<13.>	Electric heating / thermal reflection	customize the steel	
FGA15	3. 2/4/5	83	13 <r<15< td=""><td>12.5<r<15< td=""><td>Electric heating / thermal reflection</td><td>rear resistance</td></r<15<></td></r<15<>	12.5 <r<15< td=""><td>Electric heating / thermal reflection</td><td>rear resistance</td></r<15<>	Electric heating / thermal reflection	rear resistance	
FGA17	3. 2/4/5	84	16.5 <r<18.5< td=""><td>16<r<18< td=""><td>Electric heating / thermal reflection</td><td></td></r<18<></td></r<18.5<>	16 <r<18< td=""><td>Electric heating / thermal reflection</td><td></td></r<18<>	Electric heating / thermal reflection		
FGA25	3. 2/4/5	83	25 <r<28< td=""><td>23<r<27< td=""><td>Electric heating / thermal reflection</td><td>demand, which is 8-</td></r<27<></td></r<28<>	23 <r<27< td=""><td>Electric heating / thermal reflection</td><td>demand, which is 8-</td></r<27<>	Electric heating / thermal reflection	demand, which is 8-	
FGA29	3.2/4/5	85	30 <r<37< td=""><td>27. 5<r<32. 5<="" td=""><td>Electric heating / thermal reflection</td><td>1100 (0hms / sqm),</td></r<32.></td></r<37<>	27. 5 <r<32. 5<="" td=""><td>Electric heating / thermal reflection</td><td>1100 (0hms / sqm),</td></r<32.>	Electric heating / thermal reflection	1100 (0hms / sqm),	
FGA32	3. 2/4/5	85	32 <r<42< td=""><td>30. 5<r<36. 5<="" td=""><td>Electric heating / thermal reflection</td><td>and the square</td></r<36.></td></r<42<>	30. 5 <r<36. 5<="" td=""><td>Electric heating / thermal reflection</td><td>and the square</td></r<36.>	Electric heating / thermal reflection	and the square	
FGA70	3. 2/4/5	84, 5	90 <r<100< td=""><td>63<r<69< td=""><td>Electric heating</td><td>resistance</td></r<69<></td></r<100<>	63 <r<69< td=""><td>Electric heating</td><td>resistance</td></r<69<>	Electric heating	resistance	
FGA180	3, 2/4/5	83	250 <r<280< td=""><td>170<r<190< td=""><td>Electric heating</td><td>measurement is</td></r<190<></td></r<280<>	170 <r<190< td=""><td>Electric heating</td><td>measurement is</td></r<190<>	Electric heating	measurement is	









Packaging &

Shipping

Laminated Tempered Glass 6.38/10.38/16/12 /13.52 mm Low Iron Polished Edge Tempered Laminated Glass

After Sales

Service

- 1. Provide you with timely, professional, and efficient services in accordance with standardized service processes;
- 2. 7 * 24-hour hotline telephone online service;
- 3. Quality issues that belong to the production process will be unconditionally resolved;

FAQ

Q: What is the MOQ?A: Generally, there is no MOQ for processed glass, but if you want to receive the best price, the bigger quantity, the better price. Q: Can I have a small sample to verify the quality A: Sure, we welcome samples to be tested and checked for quality. Q: Can I visit your factory?A: Yes, we welcome all of the customers to visit our factory when you have real requirements, we will take you to each of our production lines, and discuss orders in our office. Q: Do you offer a guarantee for the products? A: Yes, generally, we offer 5 years warranty for processing glass based on your normal uses, we advise you use it in the right way can keep your product's service life a long time (more than 5 years). Q: How do you control the quality of your products? A: We have standard management in the factory based on the ISO system, and train our staff regularly, our production department will choose high-quality materials for glass strictly, for finished excellent products. And we have QC for each process, once find any problem, we will replace the glass, to make sure every piece of glass go to the customer's warehouse is in good condition.





15215322121



leon@qdcrglass.com



rise-glass.com

Tianzhi Building, No. 63 Beijing Road, Huangdao District, Qingdao City, Shandong Province